SIEMENS

Data sheet 6AG1803-3BA00-7AA0

product type designation	**TIM 3V-IE DNP3**
	spare part SIPLUS NET TIM 3V-IE DNP3 based on 6NH7803-3BA00-0AA0 with conformal coating, -25…+70 °C, communications module for SIMATIC S7-300 with an RS232 interface



Figure similar

product brand name	SIPLUS
Technical Product Detail Page	https://www.plcreadyship.com/?s=6AG1803-3BA00-7AA0
interfaces	
number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
● for power supply	1
type of electrical connection	
● for power supply	2-pole plugable terminal block
design of the removable storage	
● C-PLUG	No
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
consumed current	
● from external supply voltage / at DC / at 24 V / maximum	0.2 A
power loss [W]	5.8 W
ambient conditions	
ambient temperature	
● during operation	-25 ... +70 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
● with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
● conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes
resistance to mechanically active substances	

© Copyright Plcreadyship

● conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.25 kg
product features, product functions, product components / general	
number of units	
● note	Number of TIMs per S7-300: 1
performance data / S7 communication	
number of possible connections / for S7 communication	
● maximum	3; only via LAN
● with PG connections / maximum	2
performance data / telecontrol	
suitability for use	
● node station	Yes
● substation	Yes
● TIM control center	Yes
protocol / is supported	
● DNP3	Yes
product function / data buffering if connection is aborted	Yes; 64,000 data points with one master
product functions / management, configuration, engineering	
configuration software	
● required	SINAUT ST7 ES
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://www.plcreadyship.com/?s=6AG1803-3BA00-7AA0
● to web page: selection aid TIA Selection Tool	https://www.plcreadyship.com/?s=6AG1803-3BA00-7AA0
● to website: Industrial communication	https://www.plcreadyship.com/?s=6AG1803-3BA00-7AA0
● to web page: SiePortal	
● to website: Image database	https://www.plcreadyship.com/?s=6AG1803-3BA00-7AA0
● to website: CAx-Download-Manager	
● to website: Industry Online Support	https://www.plcreadyship.com/?s=6AG1803-3BA00-7AA0
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under

© Copyright Plcreadyship

. (V4.7)

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

General Product Approval

last modified: 3/10/2026

© Copyright Plcreadyship