SIEMENS

Data sheet 6AG1992-1AM00-7AA0

product type designation	**SFP992-1LD**
	SIPLUS NET SCALANCE X SFP992-1LD based on 6GK5992-1AM00-8AA0 with conformal coating, -40…+85 °C, SCALANCE X accessory; plug-in transceiver SFP992-1LD; 1x 1000 Mbps LC port, optical; single-mode optical up to max. 10 km



product brand name	SIPLUS
Technical Product Detail Page	https://www.plcreadyship.com/?s=6AG1992-1AM00-7AA0
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	1
number of optical interfaces / for network components or terminal equipment / maximum	1
number of 1000 Mbit/s LC ports / for single mode (LD) / integrated	1
design of the optical interface / for network components or terminal equipment	LC
wavelength / of the optical interface	1310 nm; Single-mode
connectable optical power relative to 1 mW	
● of the transmitter output / minimum	-9.5 dB
● of the transmitter output / maximum	-3 dB
● of the receiver input / maximum	-3 dB
optical sensitivity relating to 1 mW / of the receiver input / minimum	-19 dB
attenuation factor / of the FOC transmission link / minimum necessary	0 dB
range / at the optical interface / depending on the optical fiber used	0 ... 10 km
ambient conditions	
ambient temperature	
● during operation	-40 ... +85 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
● note	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
protection class IP	IP20
design, dimensions and weights	
design	SFP Module
width	14 mm
height	9 mm
depth	57 mm
net weight	0.01 kg
fastening method	latched
standards, specifications, approvals	
standard	
● for emitted interference	EN 61000-6-4:2007 (Class A)

Subject to change without notice
© Copyright Plcreadyship

● for interference immunity	EN 61000-6-2:2005
certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
● CE marking	Yes
MTBF	600 a

further information / internet links

internet link	
● to website: Selection guide for cables and connectors	https://www.plcreadyship.com/?s=6AG1992-1AM00-7AA0
● to web page: selection aid TIA Selection Tool	https://www.plcreadyship.com/?s=6AG1992-1AM00-7AA0
● to website: Industrial communication	https://www.plcreadyship.com/?s=6AG1992-1AM00-7AA0
● to web page: SiePortal	
● to website: Image database	https://www.plcreadyship.com/?s=6AG1992-1AM00-7AA0
● to website: CAx-Download-Manager	
● to website: Industry Online Support	https://www.plcreadyship.com/?s=6AG1992-1AM00-7AA0

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under . (V4.7)

Approvals / Certificates

General Product Approval

Manufacturer Declaration | China RoHS | China RoHS

General Product Approval	EMV	For use in hazardous locations
		CCC-Ex

last modified: 3/10/2026

© Copyright Plcreadyship