SIEMENS

Data sheet 6AG4141-3BA40-0AA0

	SIMATIC IPC427E (Microbox PC), HD graphic onboard, 4x USB V3.0 (high current), PCIE (optional), Core i3-6102E; 3x Gbit Ethernet (IE/PN) Mounting onto standard rail; 4 GB; 2x RS232/485; 1x PCIe (x4); without operating system, Without replaceable mass storage; without internal mass storage; Without SIMATIC software; 24 V DC industrial power supply
General information	
Product type designation	IPC427E
Installation type/mounting	
Mounting	DIN rail, wall mounting, portrait mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V; PELV / SELV floating
Mains buffering	
● Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Celeron G3902 (2C/2T, 1.6 GHz, 2 MB Cache); Core i3-6102E (2C/4T, 1.9 GHz, 3 MB Cache); Core i5-6442EQ (4C/4T, 1.9 (2.7) GHz, 6 MB Cache, iAMT); Xeon E3-1505L v5 (4C/8T, 2.0 (2.8) GHz, 8 MB Cache, iAMT)
Chipset	Intel C236 / Intel H110
Graphic	
Graphics controller	Intel HD graphics controller
Drives	
Hard disk	2.5" SATA ≥ 320 GB
SSD	Yes; 128 / 240 / 480 GB
Storage	
Type of memory	DDR4-2400 SO-DIMM
Main memory	4 / 8 / 16 GB, ECC optional
Capacity of main memory, max.	16 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time; optional
Hardware configuration	
Slots	
● Number of PCI slots	2; Optional
● Number of compact flash slots	1; CFast
Interfaces	
Number of industrial Ethernet interfaces	3; Ethernet (2x RJ45, optional 3x RJ45)
serial interface	Without / 2x COM (RS 232 / 485 / 422; switchable)
Video interfaces	
● Graphics interface	2x DisplayPort
Industrial Ethernet	
● Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Interrupts/diagnostics/status information	
LED status display	1x power, 3x user
Bus diagnostics	Yes
Integrated Functions	
Monitoring functions	
● Temperature monitoring	Yes
● Fan	No
● Monitoring function via network	Optional

© Copyright Plcreadyship

Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
● UL 508	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
FCC	Yes
Use in hazardous areas	
● ATEX Zone 2	Yes; for inscription on device rating plate
● ATEX Zone 22	No
● IECEx Zone 2	Yes; for inscription on device rating plate
● IECEx Zone 22	No
● CCC Ex	Yes; for inscription on device rating plate
● cULus Class I Zone 1	No
● cULus Class I Zone 2, Division 2	Yes; for inscription on device rating plate
● cULus Class II Division 2	No
● FM Class I Division 2	No
● FM Class II Division 2	No
Marine approval	
● Germanischer Lloyd (GL)	Yes
● American Bureau of Shipping (ABS)	Yes
● Bureau Veritas (BV)	Yes
● Det Norske Veritas (DNV)	Yes
● Korean Register of Shipping (KRS)	Yes
● Lloyds Register of Shipping (LRS)	Yes
● Nippon Kaiji Kyokai (Class NK)	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	55 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Vibrations	
● Vibration resistance during operation acc. to IEC 60068-2-6	tested to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm, 58 Hz to 200 Hz: 9.8 m/s² (1 g)
Operating systems	
pre-installed operating system	Windows 7 Ultimate (Multi-Language) 64-bit, Windows Embedded Standard 7 E/P 32-bit / 64-bit, Windows 10
without operating system	Yes; Optional
pre-installed operating system	
● Windows 7	Yes; Ultimate 32 bit or 64 bit
● Windows 10 Enterprise	Yes; Windows 10 Enterprise 2016 LTSB, 64 bit, MUI
Software	
Pre-installed software	Edge SW (Simatic, Sinumerik), optional
Dimensions	
Width	262 mm
Height	139.69999 mm
Depth	55.5 mm; without PCIe
Approvals / Certificates	
General Product Approval	

© Copyright Plcreadyship

Manufacturer Declaration

General Product Approval				For use in hazardous locations	
	BIS CRS				

For use in hazardous locations			Maritime application		
	Miscellaneous	CCC-Ex			

Maritime application				Dangerous goods	
	NK / Nippon Kaiji Kyokai	CCS (China Classification Society)	KR (Korean Register of Shipping)	Dangerous goods information	Test Summary Report UN 38.3

Dangerous goods		Environment	
Dangerous goods information	Test Summary Report UN 38.3	Environmental Confirmations	Environmental Confirmations

last modified: 6/10/2026

© Copyright Plcreadyship