SIEMENS

## Data sheet 6AV7241-5KA00-0DA2

SIMATIC IPC 477E 19" Multitouch (1366 x 768); 4 USB (back), Ethernet (10/100/1000); Core i5-6442EQ; 3x Gbit Ethernet (IE/PN); 4 GB without RS 232/RS485; without PCIe; without operating system; Without replaceable mass storage; 256 GB Eco SSD; Without SIMATIC software; 110/230 V AC industrial power supply unit with NAMUR; power supply cord Europe; - - no BIS certificate for India for 110/230 V AC PS,

| | |
|---|---|
| **General information** | |
| Product type designation | IPC477E |
| **Display** | |
| Design of display | 19" TFT multi-touch |
| Screen diagonal | 18.5 in |
| Resolution (pixels) | |
| ● Horizontal image resolution | 1 366 pixel |
| ● Vertical image resolution | 768 pixel |
| Backlighting | |
| ● MTBF backlighting (at 25 °C) | 50 000 h |
| **Control elements** | |
| Keyboard | |
| ● Function keys | No |
| ● alphanumeric keyboard | No |
| Touch operation | |
| ● Design as multi-touch screen | Yes; Projective-capacitive |
| **Installation type/mounting** | |
| Mounting | For horizontal and vertical mounting |
| Design | Panel PC, built-in unit |
| central design | Yes |
| distributed design | No |
| Mounting in portrait format possible | Yes |
| **Supply voltage** | |
| Type of supply voltage | 100/240 V AC (autorange) 50/60 Hz; optional 24 V DC |
| Rated value (DC) | 24 V; PELV / SELV floating |
| Line frequency | |
| ● Rated value 50 Hz | Yes |
| ● Rated value 60 Hz | Yes |
| Mains buffering | |
| ● Mains/voltage failure stored energy time | 20 ms |
| **Processor** | |
| Processor type | Celeron G3902 (2C/2T, 1.6 GHz, 2 MB Cache); Core i3-6102E (2C/4T, 1.9 GHz, 3 MB Cache); Core i5-6442EQ (4C/4T, 1.9 (2.7) GHz, 6 MB Cache, iAMT); Xeon E3-1505L v5 (4C/8T, 2.0 (2.8) GHz, 8 MB Cache, iAMT) |
| Chipset | Intel C236 / Intel H110 |
| **Graphic** | |
| Graphics controller | Intel HD graphics controller |
| **Drives** | |
| Hard disk | 2.5" SATA ≥ 320 GB |
| SSD | Yes; 128 / 240 / 480 GB |
| **Storage** | |
| Type of memory | DDR4-2400 SO-DIMM |
| Main memory | 4 / 8 / 16 GB, ECC optional |
| Capacity of main memory, max. | 16 Gbyte |
| **Data areas and their retentivity** | |
| Retentive data area (incl. timers, counters, flags), max. | 512 kbyte; 128 KB can be stored in the buffer time; optional |


© Copyright Plcreadyship

| | |
|---|---|
| **Hardware configuration** | |
| Slots | |
| ● Number of PCI slots | 1; Optional |
| ● Number of compact flash slots | 1; CFast |
| **Interfaces** | |
| Number of industrial Ethernet interfaces | 3; 3x Ethernet (RJ45) |
| serial interface | Without / 2x COM (RS 232 / 422 / 485), selectable in the BIOS |
| Video interfaces | |
| ● Graphics interface | 2x DisplayPort |
| Industrial Ethernet | |
| ● Industrial Ethernet interface | |
| — 100 Mbps | Yes |
| — 1000 Mbps | Yes |
| **Interrupts/diagnostics/status information** | |
| Bus diagnostics | Yes |
| **Integrated Functions** | |
| Monitoring functions | |
| ● Temperature monitoring | Yes |
| ● Fan | No |
| ● Monitoring function via network | Optional |
| **Degree and class of protection** | |
| IP (at the front) | IP65 |
| IP (rear) | IP20 |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| CSA approval | Yes |
| UL approval | Yes |
| ● UL 508 | Yes |
| cULus | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| FCC | Yes |
| Use in hazardous areas | |
| ● ATEX Zone 2 | Yes; for inscription on device rating plate |
| ● ATEX Zone 22 | Yes; for inscription on device rating plate |
| ● IECEx Zone 2 | Yes; for inscription on device rating plate |
| ● IECEx Zone 22 | Yes; for inscription on device rating plate |
| ● CCC Ex | Yes; for inscription on device rating plate |
| ● cULus Class I Zone 1 | No |
| ● cULus Class I Zone 2, Division 2 | Yes; for inscription on device rating plate |
| ● cULus Class II Division 2 | Yes; for inscription on device rating plate |
| ● FM Class I Division 2 | No |
| ● FM Class II Division 2 | No |
| Marine approval | |
| ● Germanischer Lloyd (GL) | Yes |
| ● American Bureau of Shipping (ABS) | Yes |
| ● Bureau Veritas (BV) | Yes |
| ● Det Norske Veritas (DNV) | Yes |
| ● Korean Register of Shipping (KRS) | Yes |
| ● Lloyds Register of Shipping (LRS) | Yes |
| ● Nippon Kaiji Kyokai (Class NK) | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 0 °C |
| ● max. | 45 °C |
| Ambient temperature during storage/transportation | |
| ● min. | -20 °C |


© Copyright Plcreadyship

| | |
|---|---|
| ● max. | 60 °C |
| Vibrations | |
| ● Vibration resistance during operation acc. to IEC 60068-2-6 | IEC 60068-2-6; 5 Hz to 9 Hz: 3.5 mm; 9 Hz to 500 Hz: 9.8 m/s² (with SSD or CFast); 10 Hz to 58 Hz: 0.0375 mm; 58 Hz to 200 Hz: 4.9 m/s² (hard disk) |
| **Operating systems** | |
| pre-installed operating system | Windows 7 Ultimate (Multi-Language) 64-bit, Windows Embedded Standard 7 E/P 32-bit / 64-bit, Windows 10 |
| without operating system | Yes; Optional |
| pre-installed operating system | |
| ● Windows 7 | Yes; Ultimate 64 bit |
| ● Windows 10 Enterprise | Yes; Windows 10 Enterprise 2016 LTSB, 64 bit, MUI |
| **Dimensions** | |
| Width of the housing front | 464 mm |
| Height of housing front | 294 mm |
| Mounting cutout, width | 448 mm |
| Mounting cutout, height | 278 mm |
| mounting depth | 76 mm |
| **Weights** | |
| Weight, approx. | 6.6 kg |
| **Approvals / Certificates** | |

| General Product Approval | | | | | Maritime application |
|---|---|---|---|---|---|
| Miscellaneous | UL | EAC | BIS CRS | China RoHS | ABS |

| Maritime application | | | | Dangerous goods | |
|---|---|---|---|---|---|
| BUREAU VERITAS | DNV | LRS | NK / Nippon Kaiji Kyokai | Dangerous goods information | Test Summary Report UN 38.3 |

**last modified:** 12/17/2025


© Copyright Plcreadyship